

Air conditioners

Heating & Cooling

Wall mounted unit

- » **Easy control at your fingertips**
- » **Turbo mode**
- » **Anti-corrosion treated outdoor unit**
- » **Wide range, from 20 to 60 class**



FTYNV-A



Fan only



Comfortable sleeping mode



Vertical auto swing



Auto fan speed



Fan speed steps



Dry programme



24 hour timer



Infrared remote control

Heating & Cooling

Indoor unit			FTYNV20A	FTYNV25A	FTYNV35A	FTYNV50A	FTYNV60A		
Cooling capacity	Nom.	kW	2.2	2.6	3.5	5.3	6.45		
Heating capacity	Nom.	kW	2.3	2.75	3.8	5.8	7.35		
Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	EER		3.24	3.21		3.42	3.12		
	COP		3.71	3.77	3.62	3.63	3.42		
Annual energy consumption		kWh	340	405	545	775	1,035		
Energy label	Cooling		A				B		
	Heating		A				B		
Dimensions	Unit	HeightxWidthxDepth	mm		265x790x174	275x845x180	298x940x200	315x1,007x219	
Weight	Unit		kg		8	9	10	13	
Fan-Air flow rate	Cooling	High/Nom./Low/Silent operation	m ³ /min		7/6.2/5.5/4.3	8.3/6.9/6/5	10.5/8.8/7.2/5.5	14.2/13/10.8/9.2	20.8/18.3/15.8/13.3
Sound pressure level	Cooling	High/Nom./Low/Silent operation	dBA		40/37/35/32	39/36/33/30	42/39/36/33	45/42/38/-	46/43/40/35
Piping connections	Liquid	OD	mm		6.35				
	Gas	OD	mm		9.52	12.7	15.9		
Power supply	Phase / Frequency / Voltage		Hz / V		1~/50/220-240				

Outdoor unit				RYNV20A	RYNV25A	RYNV35A	RYNV50A	RYNV60A
Dimensions	Unit	HeightxWidthxDepth	mm	540x771.6x320	540x848x320	592x848x320	680x913x378	700x955x424
Weight	Unit		kg	28	26	41	46	57
Compressor	Type			Rotary				
Sound pressure level	Cooling	Nom.	dBA	50			56	57
	Operation range	Cooling	Ambient	Min.~Max.	°CDB			18~43
Refrigerant	Heating	Ambient	Min.~Max.	°CWB			-7~24	
	Type	R-410A						
Piping connections	Liquid	OD	mm	6.35				
	Gas	OD	mm	9.52	12.7		15.9	
	Piping length	OU - IU	Max.	m	15	20	25	
	Level difference	IU - OU	Max.	m	5	10		
Power supply	Phase / Frequency / Voltage		Hz / V	1~/50/220-240				



Indoor unit FTYNV-A



Infrared remote control



Outdoor unit RYNV-A

Daikin has a worldwide reputation based on 90 years' experience in the successful manufacture of high quality air conditioning equipment for residential, commercial and industrial use and 56 years as a leader in heat pump technology.



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe NV. Daikin Europe NV. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe NV. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe NV.

Daikin products are distributed by: